

- carrier material is a self polymerising linseed oil (air drying)
- high colour strength
- viscosity can be adjusted as required
- organic or inorganic preparations and transparent iron oxides are available
- a range of fastness and durability properties are available, depending on end-use requirements

Preferred applications:

The main field of application is the colouration of stains, other application fields are PUR wearing parts and PUR 1 component systems.

Colour Index	Product name	Pigment content
PB 15:1	Vocaplast-L Blue	28 %
PB 15:3	Vocaplast-L Blue	25 %
PB 29	Vocaplast-L Blue	50 %
PBk 11	Vocaplast-L Black	50 %
PBk 7	Vocaplast-L Black	20 %
PG 17	Vocaplast-L Green Chromoxide	55 %
PG 7	Vocaplast-L Green	30 %
PR 101	Vocaplast-L Red	50 %
PR 101	Vocaplast-L Transoxide Red	30 %
PR 112	Vocaplast-L Red	30 %
PR 122	Vocaplast-L Red	30 %
PR 170	Vocaplast-L Red	30 %
PR 254	Vocaplast-L Red	35 %
PR 57:1	Vocaplast-L Red	20 %
PW 6	Vocaplast-L White	50 %
PY 13	Vocaplast-L Yellow	25 %
PY 184	Vocaplast-L Transoxide Yellow	25 %
PY 42	Vocaplast-L Yellow	45 %
PY 42	Vocaplast-L Transoxide Yellow	25 %
PY 74	Vocaplast-L Yellow	40 %